




REQUEST FOR QUOTATION/BID FORM

Date: May 28, 2025
 PR No.: 2025-03-539 Part
 Fund: 101
 End-User: Jena T. Perez

Project Name: PROCUREMENT OF AUDIO VISUAL EQUIPMENT & SUPPLIES FOR LIBRARY SERVICES
 ABC: One Hundred Eighty Two Thousand Eight Hundred Pesos (Php 182,800.00)
 Mode of Procurement: SHOPPING (Section 52.1(b) of the 2016 RIRR of RA 9184)
 Mode of Evaluation: Lot Evaluation
 Delivery Period: Twenty-Five (25) calendar days upon receipt of P.O.

Sir/Madam:

Please quote your lowest price on the item/s listed below, subject to the Terms and Conditions below and submit your quotation duly signed by your representative not later than **JUNE 03, 2025** sealed in an envelope.


GEMMA G. ACEDO, Ph.D.
 BAC Chairperson

- Note:**
- Bidder shall provide correct and accurate information required in this form. All entries must be typewritten or legibly written.
 - Any interlineations, erasures, or overwriting shall be valid only if they are signed or initialed by you or any of your duly authorized representative/s.
 - Price quotation/s to be denominated in Philippine peso, shall include all taxes, duties, and/or levies payable.
 - Bidder may submit, if available, original brochure showing certifications of the product being offered.
 - Quotations through email is acceptable. Winning bidder shall submit original signed RFQ before issuance of Purchase Order.
 - Documentary requirements shall be attached upon submission of the quotation:
 - Mayor's/Business Permit
 - PhilGEPS Registration Certificate
 - Income/Business Tax Returns (for ABC's above P500K)
 - Omnibus Sworn Statement (for ABC's above P50K) - for submission upon receipt of Notice of Award

Item No.	Description	QTY	UOM	BID OFFER		Offered Specs/ Brand/Model	Remarks
				Unit Price	Total Price		
1	WIRELESS MICROPHONE A. OVERALL SYSTEM OSD Mode: PULL LOCK Operating Frequency: 520MHz~(optional) Modulation Mode: FM Maximum Deviation: +45 Frequency Response: 80Hz~15KHz (+3dB)Image= Rejection: <1% Operating Temperature: -10°C~+50°C B. HANDHELD TRANSMITTER Output Power: 8~30mW Harmonic Interference Ratio: -50dB Battery: 2pcs AA Type Alkaline Battery Cartridge: Dynamic C. TIE-CLIP TRANSMITTER Output Power(Lowest): 4~6mW Output Power(Highest): 20~30mW Harmonic Interference Ratio: -50dB Battery: 2pcs AA Type Alkaline Battery Cartridge: Single Polar Pattern Capacity Microphone D. RECEIVER Sensitivity: 12dBuV(80dB S/N) Sensitivity Range: 12~32dBuV Harmonic Interference Ratio: >75dB Audio Output: Balanced: 0~0.5V/600 Audio Output: 0~0.5V/5k	1	pc				



2	PAR LIGHTS Lp001-H & LP001-H Plus great multi-beam effects and perfect for bar, pub, club, disco, mobile DJ, private parties and more operating environments. Light source : 54*3W 3-in-1 LED (R G B) ; Power supply: 100-240V, AC 50/60HZ; Control mode: Auto/ Sound/ Master-slave/ DMX/Remote control unit ; lp001:54*3W , Wire *4 , Remote control *1; LP001-PLUS : 60*3W *1 Wire *4 Remote	8	pc				
3	STAGE LIGHT CONTROLLER <ul style="list-style-type: none"> • Voltage: AC90–240V,50–60HZ • Product Size: 48.3X13.4X7 cm • Weight: 1.55 KG • Certificate:CE & ROHS & UL & SAA • Mode Number: SH03-192Console • 192 DMX Channels • 8 Programmable scenes. 8 adjustable potentiometers to adjust the output size. • built-in MIC head, and voice features • The 4 LED digital display • Automatically trigger state, the TAP SYNC button or the SPEED potentiometer to determine automatically trigger time. • The first led digit shows CHASES, the second digit led shows SCENES • The third and fourth led digit shows BANKS. • The third, fourth led digit show steps 0-255 or TIME. • BLACK OUT function can be used manually or MIDI remote control. • CHASES programming and CHASES run function can be used manually or MIDI remote control 	1	pc				
4	AMPLIFIER MODULE FOR ACTIVE SPEAKER AUDIO CENTER EA515 AMPLIFIER Amplifier Circuitry: Class D Power (Peak):2000W Frequency Response: 20Hz-20KHz (+0.5dB)(1W 8Ω 2ch) Intermodulation Distortion: <0.5% Total Harmonic Distortion:<0.5% Protection: DC protection, short circuit protection, over heat protection, input overload protection, output overload protection, soft start up protection, over voltage protection, undervoltage protection Cooling System: Cooling with fans, air convection DSP Processor: 96KHz signal sampling frequency, 24bit precision Presets cross over: MAIN, F/M Monitor, W/SUB controlled by DSP Output/Input Signal Input: 2xNEUTRIK female XLR,Mono Jack 6.35, 1xRCA Signal Output: 2xNEUTRIK male XLR Power Input: 3 pin plug Working Voltage: 100V-130V/60Hz or 220V-	3	unit				
5	HEAVY DUTY CRANK UP LIGHTING STAND WITH T-BAR SS-022 Crank Stand for Lights (Height: 1.8-4.3M, Bar 2M, Maxload: 60Kg) Height: Max 65 inches if adjusted Light Stand with Crank Load Capacity: up to 60Kgs Can increased the stand up to 46 inches Professional Lighting Stand with capacity to attach up to 4 lighting fixtures with crack for easy adjustment Good For lighting setups in clubs, pubs,	2	pc				



6	MOVING HEAD Original Beam 295 with four case Voltage: AC100V-240V, 50/60Hz Rated power: 450W Light source: 295W Beam angle: 3.8° Control channels: 18 standard DMX channels Operating mode: voice control, self-propelled, master-slave, DMX512 Color wheel: 14 colors + white light, linear color conversion and rainbow effect Pattern plate: 14 patterns + white circle Prism: Two independent prism disks (one 8 prism, one 8+16+32 prism), the prism and the prism can freely rotate forward and backward, and have prism positioning function. The prisms can be superimposed to create a composite effect. Focus adjustment: DMX linear high-definition focus, the distance and near clarity of the pattern can be adjusted freely. Atomization: The built-in atomization mirror can generate a softening effect adjustment, 0% to 100% linear atomization, with colorful effects. Strobe: Using double-chip high-speed strobe, 1- 15 times/second ultra-high-speed strobe effect. Dimming: light output lens diameter 145MM; 0- 100% mechanical linear dimming. Scanning angle: horizontal 540°, vertical 270°, 8 or 16Bit precision fine-tuning, automatic return Correction function: fast speed, smooth operation without jitter, low noise, and accurate positioning.	2	unit				
7	HEAVY DUTY SPEAKER STAND 2 Pieces Audioline Heavy Duty Speaker Stand 80kg Capacity - Adjustable Height; Model: TYS- 13a Height: 1.85 meters Sold as PAIR (either Black + red set or Black + yellow set) Color depends on what is available upon order Capacity upto 80kg	1	pair				
TOTAL BID PRICE							

After having carefully read and accepted your General Conditions, I/We submit our quotation/s for the item/s above.

Signature over Printed Name

Position/Designation

Office Mobile No. / E-mail Address

TERMS AND CONDITIONS

1. Quotations exceeding the Approved Budget for the Contract shall be rejected.
2. Award of contract shall be made to the lowest quotation which complies with the technical specifications, requirements and other terms and conditions stated herein.
3. The item/s shall be delivered according to the accepted offer of the bidder.
4. Payment shall be processed after delivery and upon submission of the required supporting documents, in accordance with existing government accounting rules and regulations.
5. Liquidated damages equivalent to one-tenth of one percent (0.1%) of the value of the goods not delivered within the prescribed delivery period shall be imposed per day of delay. The CatSU may rescind the contract once the cumulative amount of liquidated damages reaches ten percent (10%) of the amount of the contract, without prejudice to other courses of action and remedies open to it.
6. The Procuring Entity may cancel or terminate the contract at any time in accordance with the grounds provided under RA No. 9184 and its 2016 revised IRR.