

Section VII. Technical Specifications

Technical Specifications

Item	Specification	Statement of Compliance
		<i>[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.] Please state the brand and model being offered</i>
1	Premium Touch Viscolux Mattress (60"x75" Comfort: Senso Memory, Support Nuovoluxe, Cover: Tencel Knitted, Materials: Smart Reflex Pocket Springs, Senso Memory Foam, Power Edge Foam, Tencel Fabric, Thickness: 11"	
2	Premier Size Mattress (36"x75") Airlite Breeze, Semi Knitted Fabric Cover with 3D Spacer, Memory Foam, Matress Height: 6"	
3	Premier Size Mattress (36"x75") Airlite Breeze, Semi Knitted Fabric Cover with 3D Spacer, Memory Foam, Matress Height: 4"	
4	Exhaust Fan (Ceiling mounted 8" 26W 230V, 60Hz, Airflow: 8.2m3/min	
	<i>Ducting for Exhaust Fan</i>	
5	4"Ø x 3M PVC Pipe Air Duct series 1000	
6	4"Ø stainless vent cap	
7	Duct tape	
8	Exhaust Fan (Wall mounted 12" 33W 230V, 60Hz	

Item	Specification	Statement of Compliance
9	506A 60BK Range Hood, 60 cm Slim type traditional hood design, Black painted finish, Single motor, Suction power: 250m ³ /hr, Easy to clean aluminum cassette filter, Charcoal filter, 3 speed push button controls, Recirculation or ducting available, LED Lights	
	<i>Ducting for Range Hood</i>	
10	5"Ø x 3M PVC Pipe Air Duct series 1000	
11	5"Ø ventilating duct louver	
12	Duct tape	
13	E 345-004 IS Induction Cooktops, Controls: Touch controls, Equipped with booster function, Power levels: 9 (max), Adjustable power levels, Safety key-lock, Built-in timer of up to 99 minutes, Minute minder, Residual heat indicator, Pan detection indicator, Thermal protections	
14	1.0 HP Aircon Unit Wall Mounted Split Type (Cooling capacity: 9,500 BTU/Hr, Input Power (W): 780, Running current (A): 4.8, EER (BTU/W): 12.18, Power Supply (V-Hz): 230V, 60Hz, Air Volume (m ³ /min): 9.6, Dimension (mm)-Indoor (WxHxD)-877 x 292 x 222, Dimension (mm)-Outdoor (WxHxD) 598 x 495 x 265	
NOTE: ITEMIZED EVALUATION		

I hereby certify that the statement of compliance to the foregoing technical specifications are true and correct, otherwise, if found to be false during bid evaluation or post-qualification, the same shall give rise to automatic disqualification of our bid.

Name of Company

Signature over Printed Name of
Authorized Representative

Date

